

DECLARATION OF PERFORMANC Nro. 003CPRSB

Nordic Fibreboard Ltd OÜ

01.01.2021

1. Unique identification code of the product-type: Fibreboard

Underlay / Põrandaplaat / Lattijaleijona / Lattialevy / Lydiso

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number is provided on the packaging.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification:

Softboard for general purpose boards for use in dry condition (tehnical class SB)

4. Name and contact address of the manufacturer as required pursuant to Article 11(5):

Nordic Fibreboard Ltd OÜ Rääma 31, 80044 Pärnu Tel. + 372 445 1800 info@nordicfibreboard.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

contact the manufacturer.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3.

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

not applicable.

8. ETA:

not applicable.

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Bending strength	≥ 2,5 N/mm ²	EN 13986:2004
Tensile strength	≥ 0,02 N/mm ²	
Swelling in thickness	≤ 10 %	
Release of formaldehyde	Class E1	
Reaction to fire	Euroclass E	
Thermal conductivity	0,049 W/(m · K)	
Water vapour permeability	Dry cup μ = 5	
Sound absorption	250Hz-500Hz - 0,10 1000Hz-2000Hz - 0,30	
Impact sound insulation	$\Delta L_W = 18 \text{ dB}$ $I_{\Delta I} = 22 \text{ dB}$	RTE 11202/97; VTT-S-06861-11

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

