

**DECLARATION OF PERFORMANCE**  
**No. 006CPRF**

Nordic Fibreboard Ltd OÜ 01.01.2021

1. Unique identification code of the product-type:

**Isotex interior finishing board**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Isotex ceiling board / Batch number is provided on the packaging.**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification:

**EN 13171:2012. Thermal insulation products for buildings – Factory made wood fibre (WF) products – Specification**

4. Name and contact address of the manufacturer as required pursuant to Article 11(5):

**Nordic Fibreboard Ltd OÜ  
Rääma 31, 80044 Pärnu  
Tel. + 372 445 1800**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**contact the manufacturer.**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 4.**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**Inspecta Estonia OÜ (Notified body nr 1336 ) has performed inspection of the factory production control, performs the continuous surveillance, assessments and approval of factory production control.**

8. ETA:

**not applicable.**

9. Declared performance:

Title	Essentia characteristics	Performance	Harmonised standard
Reaction to fire	4.2.6 Reaction to fire	<b>Euroclass D-s1, d0</b>	EN 13171:2012
Release of dangerous substances to the indoor environment	4.3.15 Release of dangerous substances	<b>Fulfills requirements of Classification of Indoor Climate 2008 and the Classification of Building Materials</b>	Test report VTT- S-02769- 12; VTT-S - 04710- 07; VTT-S-09053- 06
Acoustic absorption index	4.3.12 Sound absorption	<b>aw ≥ 0,10</b>	EN 13171 : 2012
Direct airborne sound insulation index	4.3.13 Air flow resistivity	<b>AFr100</b>	
Thermal resistance	4.2.1 Thermal resistance and thermal conductivity	<b>R=0,20 m<sup>2</sup>·K/W λD=0,049 W/(m·K)</b>	
	4.2.3 Thickness	<b>As shown in the label</b>	
Water permeability	4.3.8 Water absorption	NPD	
Water vapour permeability	4.3.9 Water vapour transmission	<b>MU5</b>	
Compressive strength	4.3.3 Compressive stress or compressive strength	NPD	
	4.3.6 Point load	NPD	
Durability of reaction to fire against heat, weathering, ageing/degradation	4.2.7 Durability characteristics <sup>a, b</sup>	<b>Euroclass D-s1, d0</b>	
Durability of thermal resistance against heat, weathering, ageing/degradation	4.2.1 Thermal resistance and thermal conductivity <sup>c</sup>	NPD	
	4.3.2.2 Dimensional	<b>DS(70,-)1</b>	

	stability under specified temperature <sup>d</sup>	
Tensile/Flexural strength	4.3.5 Tensile strength parallel to faces <sup>e</sup>	NPD
Durability of Compressive strength against ageing/degradation	4.3.7 Compressive creep	<b>CC(3,5/3,0/10)70</b>

- a) No change in Reaction to fire properties for wood fibre products.
- b) The fire performance of wood fibre products does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- c) Thermal conductivity of wood fibre products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air.
- d) For thickness only.
- e) This characteristic also covers handling and installation.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:




---

Kristina Kivimeister, Production Director  
Pärnu, 01.01.2021